

HEMPEL'S ANTI-SLIP BEADS 67420

Description:	HEMPEL'S ANTI-SLIP BEADS 6742 are hollow, aluminium silicate spheres ("glass pearls") of diameters between 5 and 200 micron.
Recommended use:	To obtain anti-skid properties on decks and other areas where a skid-proof surface is required. To be mixed with the paint before application.
Availability:	Subject to confirmation.

PHYSICAL CONSTANTS:

Colour:	Off-white/greyish
Specific gravity:	0.7 kg/litre (approx.)
Particle shape:	Spherical

REMARKS:	<p>Store under dry and clean conditions.</p> <p>Use approximately the following amount in weight of HEMPEL'S ANTI-SLIP BEADS 6742:</p> <p>Approx. 0.8 kg/1.8 lbs of HEMPEL'S ANTI-SLIP BEADS 6742 into 20 litres or 5 US gallons of HEMPATEX ENAMEL 5636.</p> <p>Approx. 1.0 kg/2.2 lbs of HEMPEL'S ANTI-SLIP BEADS 6742 into 20 litres or 5 US gallons of HEMPATEX HI-BUILD 4641 or of HEMPALIN DECKPAINT 5324.</p> <p>Approx. 1.2 kg/2.6 lbs of HEMPEL'S ANTI-SLIP BEADS 6742 into 20 litres or 5 US gallons of HEMPEL'S B/T COATING 5118 or of HEMPATHANE TOPCOAT 5521.</p> <p>Approx. 1.3 kg/2.9 lbs of HEMPEL'S ANTI-SLIP BEADS 6742 into 20 litres or 5 US gallons of HEMPADUR HI-BUILD 4520.</p> <p>HEMPEL'S ANTI-SLIP BEADS 6742 must be stirred thoroughly into the paint until a uniform mixture has been obtained.</p> <p>Apply the mixture by brush, by roller, or by conventional spray equipment using pressure vessel and large nozzle orifice.</p>
-----------------	--

Note:	HEMPEL'S ANTI-SLIP BEADS 6742 is for professional use only.
--------------	--

This Product Data Sheet supersedes those previously issued. For definition and scope, see explanatory notes to applicable Product Data Sheets.

Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User. The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.

Issued by HEMPEL'S MARINE PAINTS A/S.

*This is a corporate trademark of the Hempel Group.

September 1996