

HEMPEL'S LIGHT CLEAN 9935₀

Description:	HEMPEL'S LIGHT CLEAN 9935 is a solvent-free concentrated alkaline cleaner based on emulsifiers, surface-active agents and water. The product is biodegradable.
Recommended use:	For cleaning and degreasing of painted surfaces before recoating. Especially suited for removal of dirt, soot and u.v. light degraded surface-layers. Suited for use in high pressure cleaning equipment.
Availability:	Subject to confirmation.
PHYSICAL CONSTANTS:	
Colours/Shade nos:	Transparent/00000
Flash point:	Non-flammable
Specific gravity:	1.1 kg/litre 9.2 lbs/US gallon
pH value:	Approximately 12 undiluted
V.O.C.:	0 g/litre - 0 lbs/US gallon
APPLICATION METHOD:	Apply by stiff brush or by spraying using lowest possible pressure. To be diluted with fresh water: 1-20 parts of fresh water to 1 part of HEMPEL'S LIGHT CLEAN 9935. After 5 minutes the surface must be high pressure hosed with fresh water or carefully scrubbed with plenty of fresh water until all residues have been removed. If HEMPEL'S LIGHT CLEAN 9935 leaves a white film, it can be removed with warm water.
REMARKS:	Not suited for cleaning of aluminium. Do not expose to frost.
Note:	HEMPEL'S LIGHT CLEAN 9935 is for professional use only.
SAFETY:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Material Safety Data Sheets and follow all local or national safety regulations. Harmful or fatal if swallowed; immediately seek medical assistance if swallowed. Avoid inhalation of possible solvent vapours or paint mist, as well as paint contact with skin and eyes. Apply only in well ventilated areas and ensure that adequate forced ventilation exists when applying paint in confined spaces or when the air is stagnant. Always take precautions against the risks of fire and explosions.

This Product Data Sheet supersedes those previously issued. For definition and scope, see explanatory notes to applicable Product Data Sheets.

Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User. The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.

Issued by HEMPEL'S MARINE PAINTS A/S.

*This is a corporate trademark of the Hempel Group.

September 1996 - 9935000000CO003